

Entailment Graph Learning with Textual Entailment and Soft Transitivity

Zhibin Chen¹²³ Yansong Feng^{13*} Dongyan Zhao¹²³

¹Wangxuan Institute of Computer Technology, Peking University, China

²Center for Data Science, Peking University, China

³The MOE Key Laboratory of Computational Linguistics, Peking University, China

{czb-pekings, fengyansong, zhaody}@pku.edu.cn

Abstract

Typed entailment graphs try to learn the entailment relations between predicates from text and model them as edges between predicate nodes. The construction of entailment graphs usually suffers from severe sparsity and unreliability of distributional similarity. We propose a two-stage method, Entailment Graph with Textual Entailment and Transitivity (EGT2). EGT2 learns local entailment relations by recognizing possible textual entailment between template sentences formed by typed CCG-parsed predicates. Based on the generated local graph, EGT2 then uses three novel soft transitivity constraints to consider the logical transitivity in entailment structures. Experiments on benchmark datasets show that EGT2 can well model the transitivity in entailment graph to alleviate the sparsity issue, and lead to significant improvement over current state-of-the-art methods¹.

1 Introduction

Entailment, as an important relation in natural language processing (NLP), is critical to semantic understanding and natural language inference (NLI). Entailment relation has been widely applied in different NLP tasks such as Question Answering (Pathak et al., 2021; Khot et al., 2018), Machine Translation (Padó et al., 2009) and Knowledge Graph Completion (Yoshikawa et al., 2019). When coming across a question that "Which medicine cures the infection?", one can recognize the information "Griseofulvin is preferred for the infection," in the corpus and appropriately write down the answer with the knowledge that "is preferred for" entails "cures" when their arguments are medicines and diseases, although the surface form of predicate "cures" does not exactly appear in the corpus. There are many ways to present one question, and it is impossible to handle them without understanding

* Corresponding author.

¹Our code is available at <https://github.com/ZacharyChenpk/EGT2>.




Figure 1: A simple example of entailment graph with types *medicine* and *disease*. The dashed line represents a missing entailment recovered by considering the transitivity constraint (red) based on the two premise entailment between three **boldfaced** predicates.

the entailment relations behind the predicates. Previous works on analyzing entailment mainly focus on Recognizing Textual Entailment (RTE) between pairs of sentences, and many recent attempts have achieved quite promising performance in detecting entailment relations using transformer-based language models (He et al., 2020; Raffel et al., 2020; Schmitt and Schütze, 2021b).

By modeling typed predicates as nodes and entailment relations as directed edges, the **Entailment Graph (EG)** is a powerful and well-established form to represent the context-independent entailment relations between predicates and reflect the global features of entailment inference, such as paraphrasing and transitivity. As EGs are able to help reasoning without additional context or resource, they can be seen as a special type of structural knowledge in natural language. Figure 1 shows an excerpt entailment graph about two types of arguments, *Medicine* and *Disease*. Generally speaking, an entailment graphs can be built based on a three-step process: **extracting** predicate pairs from a corpus, building **local** graphs with locally computed entailment scores, and modifying the graphs with **global** methods.

However, existing EG construction methods still face challenges in both local and global stages. The Distributional Inclusion Hypothesis (DIH) about entailment assumes that given a predicate (rela-

tion) p , it can be replaced in any context by another predicate (relation) q if and only if p entails q (Geffet and Dagan, 2005). Most local methods in previous works are guided by DIH, thus rely on the distributional co-occurrences from corpora, including named entities, entity pairs and context, as features to compute the *local* entailment scores. Since different predicate pairs are processed independently, the locally built graphs suffer from severe **data sparsity**. That is, there are many entailment relations missing (as edges) in the graphs if the predicate pairs do not co-occur in the corpus. Furthermore, predictions from local models may not be coherent with each other, for example, a local model may output three predictions like, a entails b , b entails c and c entails a at the same time, which actually indicate possible errors among the local predictions.

To overcome the challenges faced by local models, different global approaches are used to take the interactions and dependencies between entailment relations into consideration. The first discussed global dependency is the logical *transitivity* among different predicates, that is, predicate a entails predicate c if there is another predicate b making both " a entails b " and " b entails c " hold simultaneously. Berant et al. (2011) uses the Integer Linear Programming (ILP) to ensure the transitivity constraints on the entailment graphs, which is, unfortunately, not scalable on large graphs with thousands of nodes. Hosseini et al. (2018) models the structural similarity across graphs and paraphrasing relations within graphs to learn the global consistency, but does not gain further improvement due to the lack of **high-quality local graphs** and proper **transitivity** modeling.

In order to deal with the problems in the local and global stages, we propose a novel entailment graph learning approach, **Entailment Graph with Textual Entailment and Transitivity (EGT2)**. EGT2 builds high-quality local entailment graphs by inputting predicates as sentences into a transformer-based language model fine-tuned on an RTE task to avoid the unreliability of distributional scores, and models the global transitivity on these scores through carefully designed soft constraint losses, which alleviate the data sparsity and are feasible on large-scale local graphs. Our key insight is that the entailment relation $a \rightarrow c$ correctly implied by the transitivity constraint is based on two conditions: (1) the appropriate constraint

scalable on large graphs containing rich information, and (2) the reliability of local graphs offering the premise $a \rightarrow b$ and $b \rightarrow c$, which is impractical for previous distributional approaches, but may be available for the models well-behaved on RTE tasks. Specifically, the input sentences fed to transformer-based language models are formed without context, which makes our method accessible to those predicates not appearing in the corpus. The transitivity implication is confined to entailment relations with high confidence, which improves the quality of implied edges and cuts down the computational overheads. In a word, this paper makes the following contributions:

- we present a novel approach based on textual entailment to scoring predicate pairs on local entailment graphs, which is reliable without distributional features and valid for arbitrary predicate pairs.
- we present three carefully designed global soft constraint loss functions to model the transitivity among entailment relations on large entailment graphs, thus alleviate the data sparsity issue of previous local approaches.
- we evaluate our method on benchmark datasets, and show that our EGT2 significantly outperforms previous entailment graphs construction approaches. The further analysis proves that our local and global approaches are both useful for learning entailment graphs.

2 Related Work

Based on DIH, previous works extract feature vectors for typed predicates to compute the local distributional similarity. The set of entity argument pair strings, like "*Griseofulvin-infection*" in the example of Section 1, are used as the features weighted by Pointwise Mutual Information (Berant et al., 2015; Hosseini et al., 2018). Given the feature vectors for a predicate pair, different similarity scores, like cosine similarity, Lin (Lin, 1998), DIRT (Lin and Pantel, 2001), Weeds (Weeds and Weir, 2003) and Balanced Inclusion (Szpektor and Dagan, 2008), are calculated as the local similarities. Hosseini et al. (2019) and Hosseini et al. (2021) use Markov Chain on an entity-predicate bipartite graph weighted by link prediction scores to calculate the transition probability between two predicates as the local score. They rely on the link

predication model to generate the features in fact. [Guillou et al. \(2020\)](#) adds temporal information into entailment graphs by extracting entity pairs within a limited temporal window as predicate features. [McKenna et al. \(2021\)](#) extends the graphs to include entailment relations between predicates with different numbers of arguments by splitting the features from argument pairs into independent entity slots, which impairs the representation ability of features when unary predicates are involved.

As mentioned in Section 1, entailment graphs are generally learned by imposing global constraints on the local entailment relations about extracted predicates. The transitivity in entailment graphs is modeled by the Integer Linear Programming (ILP) in [Berant et al. \(2011\)](#), which selects a transitive sub-graph of a local weighted graph to maximize the summation over the weights of its edges. Their work is limited to a few hundreds of predicates due to the computational complexity of ILP. For better scalability, [Berant et al. \(2012\)](#) and [Berant et al. \(2015\)](#) make a strong FRG-assumption that *if predicate a entails predicates b and c, b and c entail each other*, and an approximation method, called Tree-Node-Fix (TNF). Obviously, the assumption is too strong to be satisfied by real cases.

Since the hard constraints are difficult to work well on large-scale entailment graphs, [Hosseini et al. \(2018\)](#) propose two global soft constraints that maintain the similarity between paraphrasing predicates within typed graphs and between predicates with the same names in graphs with different argument types. Their soft constraints are also used in [Hosseini et al. \(2019\)](#) and [Hosseini et al. \(2021\)](#). The similarity between paraphrasing predicates, which ensures $(a \rightarrow c) \odot (b \rightarrow c)$ and $(c \rightarrow a) \odot (c \rightarrow b)$ when $a \leftrightarrow b$, implicitly takes the transitivity between paraphrasing predicates and third predicate into consideration. But it ignores the transitivity in more common cases, and leads to a limited improvement on performance.

Meanwhile, the transformer-based Language Model (LM), although proved to be effective in RTE tasks ([He et al., 2020](#); [Raffel et al., 2020](#); [Schmitt and Schütze, 2021b](#)), has received less attention in entailment graph learning. [Schmitt and Schütze \(2021a\)](#) uses pretrained LM on the Lexical Inference in Context (LiC) task, which is closely related to entailment graph learning. [Hosseini et al. \(2021\)](#) uses pretrained BERT to initialize the contextualized embeddings in their contextualized link

prediction and entailment score calculation. Higher scores are assigned to the entailed predicates in the context of their premises, which is one implicit expression form of DIH and different from our direct utilization of LM on textual entailment.

3 Our Method: EGT2

3.1 Definition and Notations

The goal of entailment graph learning is to extract predicates, learn the entailment relations and build entailment graphs from raw text corpora. Following previous works ([Hosseini et al., 2018, 2019](#)), we use the binary relations from neo-Davisonian semantics as predicates, which is a type of first-order logic with event identifiers. For instance, with the semantic parser (here, GraphParser ([Reddy et al., 2014](#))), the sentence:

"Griseofulvin is preferred for the infection."

can be transformed into the logical form

$$\begin{aligned} \exists e. prefer_2(e, Griseofulvin) \\ \cap prefer_{for}(e, infection) \end{aligned}$$

where e denotes an event. By considering a relation for each pair of extracted arguments, this sentence refers to one predicate, $p = (prefer_2, prefer_{for}, 2, medicine, disease)$ ². Likely, the sentence *"Griseofulvin cures the infection."* contains $q = (cure.1, cure.2, medicine, disease)$. Formally, a predicate with argument types t_1 and t_2 is represented as $p = (w_{p,1} \cdot i_{p,1}, w_{p,2} \cdot i_{p,2}, t_1, t_2)$. The event-based predicate form is strong enough to describe most of the relations in real cases ([Parsons, 1990](#)).

With T as the set of types and P as the set of all typed predicates, $V(t_1, t_2)$ contains typed predicates p with unordered argument types t_1 and t_2 , where $p \in P$ and $t_1, t_2 \in T$. For predicate $p = (w_{p,1} \cdot i_{p,1}, w_{p,2} \cdot i_{p,2}, t_1, t_2)$, we denote that $\tau_1(p) = t_1$, $\tau_2(p) = t_2$ and $\pi(p) = (w_{p,1} \cdot i_{p,1}, w_{p,2} \cdot i_{p,2})$. In other words, $V(t_1, t_2) = \{p | (\tau_1(p) = t_1 \wedge \tau_2(p) = t_2) \vee (\tau_1(p) = t_2 \wedge \tau_2(p) = t_1)\}$.

A typed entailment graph $G(t_1, t_2) = \langle V(t_1, t_2), E(t_1, t_2) \rangle$ is composed of the nodes of typed predicates $V(t_1, t_2)$ and the weighted edges $E(t_1, t_2)$. The edges can be also represented as sparse score matrix $W(t_1, t_2) \in [0, 1]^{|V(t_1, t_2)| \times |V(t_1, t_2)|}$, containing the entailment scores between predicates with type t_1 and t_2 . As

²The numbers after the predicate words are corresponding argument positions of entity "Griseofulvin" (second argument of *prefer*) and "infection" (second argument of the preposition *for*), and the later two items are the types of arguments.

Table 1: Examples of sentence generator S .

Predicates	Sentences
(be.1,be.capital.of.2,location ₁ ,location ₂)	Location A is capital of Location B.
(contain.1,contain.2,location ₂ ,location ₁)	Location B contains Location A.
(prefer.2,prefer.for.2,medicine,disease)	Medicine A is preferred for Disease B.
(give.2,give.3,person,thing)	Person A is given Thing B.
(aggrieved.by.2,aggrieved.felt.1,thing,person)	Person B feels aggrieved by Thing A.

the different argument types can naturally determine whether two predicates have the same order of arguments, the order of argument type is not important while $t_1 \neq t_2$, and therefore we can ensure that $G(t_1, t_2) = G(t_2, t_1)$. For those predicates p with $\tau_1(p) = \tau_2(p)$, the two argument types are labeled with orders, which allows the graph to contain the entailment relations with different argument orders, like $(be.1,be.capital.of.2,location_1,location_2) \rightarrow (contain.1,contain.2,location_2,location_1)$.

3.2 Local Entailment based on Textual Entailment

Inspired by the outstanding performance of pre-trained and fine-tuned LMs on RTE task, which is closely related to the entailment graphs, EGT2 uses fine-tuned transformer-based LM to calculate the local entailment scores of typed predicated pairs.

In order to utilize the knowledge about entailment relations in pretrained and fine-tuned LM, EGT2 firstly transfers the predicate pair (p, q) into corresponding sentence pair $(S(p), S(q))$ by sentence generator S , as the complicated predicates cannot be directly input into the LM. For typed predicate $p = (w_{p,1} \cdot i_{p,1}, w_{p,2} \cdot i_{p,2}, t_1, t_2)$, the generator deduces the positions of arguments about the predicate based on $i_{p,1}$ and $i_{p,2}$, generates the surface form of p based on $w_{p,1}$ and $w_{p,2}$, and finally concatenates the surface form with capitalized types as its arguments. Some generated examples are shown in Table 1, and the detailed algorithm of S is described in Appendix A.

After generating sentence pair $(S(p), S(q))$ for predicate pair (p, q) , EGT2 inputs $(S(p), S(q))$ into a transformer-based LM to calculate the probability of the entailment relation $p \rightarrow q$ as the local entailment score in $G(t_1, t_2)$. In our experiments, the LM is implemented as DeBERTa (He et al., 2020). Generally, an entailment-oriented LM will output three scores for a sentence pair, representing the probability of relationship *entail*, *contradict* and *neutral* respectively. Formally, we denote

the weighted matrix of local entailment graph with type t_1 and t_2 as W^{local} , and the weight of the edge between p and q in W^{local} is calculated as:

$$W_{p,q}^{local} = P(p \rightarrow q) \in [0, 1],$$

$$P(p \rightarrow q) = \frac{e^{LM(entail|p,q)}}{\sum_{r \in \{entail, contradict, neutral\}} e^{LM(r|p,q)}}, \quad (1)$$

where $LM(r|p, q)$ is the output score of corresponding relationship by the LM. As the local entailment is based on the LM fine-tuned to perform textual entailment, the local graph can be built for any predicates in the parsed semantic form, or in any other forms by changing sentence generator S .

3.3 Global Entailment with Soft Transitivity Constraint

Existing approaches use global learning to find correct entailment relations which are missing or underestimated in local entailment graphs to overcome the data sparsity. Following Hosseini et al. (2018), the evidence from existing local edges with high confidence is used by EGT2 to predict missing edges in the entailment graphs.

The *transitivity* in entailment relation inference implies $a \rightarrow c$ while both $a \rightarrow b$ and $b \rightarrow c$ hold. For instance, in the example of Figure 1, the entailment "*is preferred for*" \rightarrow "*is effective for*" is discovered because "*is preferred for*" \rightarrow "*cures*" and "*cures*" \rightarrow "*is effective for*" have been learned. The key challenge to incorporate the transitivity constraint into weighted graphs is discreteness of logical rules. Discreteness makes the rules impossible to be directly used in gradient-based learning methods without NP-hard complexity, as different predicate pairs are jointly involved in the calculation. To unify the discrete logical rules with gradient-based learning, inspired by Li et al. (2019), EGT2 uses the logical constraints in the form of differentiable triangular norms (Gupta and Qi, 1991; Klement et al., 2013), or called t-norms, as the

$$\begin{aligned}
L_1 &= -\log \prod_{\substack{a,b,c \in V(t_1, t_2), \\ W_{a,b}, W_{b,c} > 1-\epsilon}} \min(1, \frac{W_{a,c}}{W_{a,b}W_{b,c}}) \\
&= \sum_{a,b,c \in V(t_1, t_2)} I_{1-\epsilon}(W_{a,b})I_{1-\epsilon}(W_{b,c})ReLU(\log W_{a,b} + \log W_{b,c} - \log W_{a,c}) \\
L_2 &= \sum_{a,b,c \in V(t_1, t_2)} -I_{1-\epsilon}(W_{a,b})I_{1-\epsilon}(W_{b,c})I_0(W_{a,b}W_{b,c} - W_{a,c})\log W_{a,c} \\
L_3 &= \sum_{a,b,c \in V(t_1, t_2)} -I_{1-\epsilon}(W_{a,b})I_{1-\epsilon}(W_{b,c})I_0(W_{a,b}W_{b,c} - W_{a,c})W_{a,b}W_{b,c}\log W_{a,c}
\end{aligned} \tag{2}$$

soft constraints so that the gradient-based learning methods can be applied.

Different t-norm methods transfer the discrete rules into different continuous loss functions. Traditional product t-norm maps $P(A \wedge B)$ into $P(A)P(B)$, $P(A \vee B)$ into $P(A) + P(B) - P(A)P(B)$, and $P(A \rightarrow B)$ into $\min(1, \frac{P(B)}{P(A)})$. For the entailment relations, the probability of transitivity to be satisfied is:

$$\begin{aligned}
&P[(a \rightarrow b \wedge b \rightarrow c) \rightarrow (a \rightarrow c)] \\
&= \min(1, \frac{W_{a,c}}{W_{a,b}W_{b,c}}),
\end{aligned} \tag{3}$$

where the probability of the entailment relation $a \rightarrow b$ is represented by the local entailment scores $W_{a,b}$. To alleviate the noise from those edges assigned low confidence by local LM, EGT2 only takes the local edges whose scores are higher than $1 - \epsilon$ into account (as $a \rightarrow b$ and $b \rightarrow c$), where ϵ is a small hyper-parameter because the local probability scores tend to be close to 0 or 1 in practice. Therefore, to maximize the probability of transitivity constraint satisfied over all predicates in the entailment graph $G(t_1, t_2)$, EGT2 tries to minimize the following minus-log-likelihood loss function L_1 in Eq. 2, where $I_y(x) = 1$ if $x > y$, or 0 otherwise.

Another important t-norm, called the Gödel t-norm, maps $P(A \rightarrow B)$ into 1 if $P(B) \geq P(A)$ or $P(B)$ otherwise. Therefore, the Gödel probability of transitivity to be satisfied is:

$$\begin{aligned}
&P[(a \rightarrow b \wedge b \rightarrow c) \rightarrow (a \rightarrow c)] \\
&= \begin{cases} W_{a,c} & W_{a,b}W_{b,c} > W_{a,c} \\ 1 & otherwise \end{cases},
\end{aligned} \tag{4}$$

and EGT2 similarly tries to minimize the loss function L_2 in Eq. 2. It should be noted that transitivity constraints will be disobeyed not only by the missing edges, but also by the spurious edges in the

local graphs. Therefore, we expect the soft constraints to take reducing the weights of premise edges into consideration. L_1 achieves this by the loss item $W_{a,b}$ and $W_{b,c}$, and we modify L_2 to L_3 in Eq. 2 so that the low confidence of $W_{a,c}$ will help to detect whether $W_{a,b}$ and $W_{b,c}$ are spurious. Our t-norm soft constraints, although do not guarantee the obedience of transitivity, are effective approximations for the transitivity property.

Given the local entailment graph $G(t_1, t_2)$ with weighted edges W^{local} , in order to ensure that the global entailment graph W is not too far from W^{local} , EGT2 finally minimizes the following loss function L to trade off the distance from local graphs and the soft transitivity constraint:

$$L = \sum_{a,b \in V} (W_{a,b} - W_{a,b}^{local})^2 + \lambda L_i, \quad i = 1, 2, 3 \tag{5}$$

where L_i is the specified implementation of soft transitivity constraint in Eq. 2, and λ is a non-negative hyper-parameter that controls the influence of two loss terms.

4 Experimental Setup

4.1 Predicate Extraction

Following Hosseini et al. (2018) and Hosseini et al. (2019), we use the multiple-source NewsSpike corpus (Zhang and Weld, 2013), which contains 550K news articles, to extract binary relations as generated predicates in EGT2. We make use of the triples released and filtered in Hosseini et al. (2019), which applies GraphParser (Reddy et al., 2014) based on Combinatorial Categorical Grammar (CCG) syntactic derivations to extracting binary relations between predicates and arguments. The argument entities are linked to Freebase (Bollacker et al., 2008) and mapped to the first level of FIGER types (Ling and Weld, 2012) hierarchy. The type

of a predicate is determined by its two corresponding argument entities. The triples are filtered by two rules to remove the noisy binary relations and arguments: (1) we only keep those argument-pairs appearing in at least 3 relations; (2) we only keep those relations with at least 3 different argument-pairs. The number of relations in the corpus is reduced from 26M to 3.9M, covering 304K typed predicates in 355 typed entailment graphs. Only those predicate pairs co-occurring with at least one same entity-pair (e.g., *Griseofulvin-infection*) will be linked to calculate the local scores, and as a result, our local predicate pairs are identical with Hosseini et al. (2019). As we focus on using global models to alleviate the sparsity of local edges, more potential methods to extracting denser local edges will be studied in our future research.

4.2 Evaluation Datasets and Metrics

We use Levy/Holt Dataset (Levy and Dagan, 2016; Holt, 2018) and Berant Dataset (Berant et al., 2011) to evaluate the performance of entailment graph models.

In Levy’s dataset, each example contains a pair of triples with the same entities but different predicates. Some questions with one predicate were shown to the annotating workers, like “Which medicine cures the infection?”. The label for each example are either *True* or *False*, indicating whether the first typed predicate entails the second one, by asking the workers whether the first predicates can answer the question with the second one. For example, if “Griseofulvin is preferred for the infection” is a correct answer of the above question, the dataset labels “is preferred for” \rightarrow “cures”. Holt (2018) re-annotates Levy’s dataset and forms a new dataset with 18,407 examples (3,916 positive and 14,491 negative), referred as Levy/Holt Dataset. The dataset is split into validation set (30%) and test set (70%) as Hosseini et al. (2018) in our experiments.

Berant et al. (2011) annotates all the entailment relations in their corpus, which generates 3,427 positive and 35,585 negative examples, referred as Berant Dataset. Their entity types do not exactly match with the first level of FIGER types hierarchy, and therefore a simple hand-mapping by Hosseini et al. (2018) is used to unify the predicate types.

To be comparable with previous works, we evaluate our methods on the test set of Levy/Holt Dataset and the whole Berant Dataset by calcu-

lating the area under the curves (AUC) with changing the classification threshold of global entailment scores. Hosseini et al. (2018) argues that the AUC of Precision-Recall Curve (PRC) for precisions in the range $[0.5, 1]$, as predictions with higher precision than *random* are more important for the downstream applications. Therefore, we report both the AUC of PRC for precisions in the range $[0.5, 1]$ and the traditional AUC of ROC, which is more widely used in evaluation of other tasks.

4.3 Comparison Methods

We compare our model with existing entailment graph construction methods (Berant et al., 2011; Hosseini et al., 2018, 2019, 2021) and the best local distributional method, Balanced Inclusion (Szepektor and Dagan, 2008), referred as BInc. We also include ablation variants of our EGT2, including local models with or without fine-tuning.

4.4 Implementation Details

For local transformer-based LM, EGT2 uses DeBERTa (He et al., 2020) implemented by the Hugging Face transformers library (Wolf et al., 2019)³, which has been fine-tuned on MNLI (Williams et al., 2018) dataset. In order to adapt it to the special type-oriented sentence pattern generated by S , we expand the validation set by extracting all of the predicates, generating sentence pairs by generator S for every two predicates, and checking whether they are labeled as paraphrase or entailment in the Paraphrase Database collection (PPDB) (Pavlick et al., 2015). We split 80% of the generated corpus to fine-tune the DeBERTa with Cross-Entropy Loss, and the rest as the validation set of fine-tuning process. The fine-tuning learning rate $\alpha_f = 10^{-5}$, and the process is terminated while the F_1 score of *entail* on validation set does not increase in 10 epochs or training after 100 epochs.

For global soft transitivity constrains, we use SGD (Cun et al., 1998) to optimize the scores W in entailment graphs with loss function L in Eq. 5 for $e = 5$ epochs. The SGD learning rate $\alpha = 0.05$, the coefficient $\lambda = 1$, and the confidence threshold $\epsilon = 0.02$. The hyper-parameters are selected based on Levy/Holt validation dataset. More implementation details are given in Appendix B.

For testing, if one or both predicates of the example do not appear in the corresponding typed entailment graph, we handle the example as un-

³<https://github.com/huggingface/transformers>

Table 2: Model performance on Levy/Holt Dataset and Berant Dataset. The best performances on every metric are **boldfaced**. Results with * are from the original papers.

Methods	Levy/Holt		Berant	
	PRC	ROC	PRC	ROC
BInc	.155	.632	.147	.677
Local-Sup	.161	.632	.129	.651
Hosseini18	.163	.637	.174	.682
Hosseini19*	.187	-	-	-
- Local	.167	.639	.118	.378
Hosseini21*	.195	-	-	-
EGT2-Local	.313	.712	.360	.857
- w/o Fine-tuning	.234	.673	.147	.732
EGT2- L_1	.345	.761	.437	.880
EGT2- L_2	.319	.755	.361	.879
EGT2- L_3	.356	.755	.443	.871

typed one by resorting to its average score among all typed entailment graphs. This setting is also used for all local and global methods in the experiments for fair comparison.

5 Experiment Results and Discussion

5.1 Main Results

We summarize the model performances on both Levy/Holt and Berant datasets in Table 2. All global methods, including Hosseini et al. (2018), Hosseini et al. (2019) and EGT2, perform better than their corresponding local methods, which demonstrates the effect of global constraints in alleviating the data sparsity. Although using the same extracted entailment relations with Hosseini et al. (2019), our EGT2-Local significantly outperforms previous local methods because of the high-quality entailment scores generated by reliable fine-tuned textual entailment LM. On the whole, EGT2 with transitivity constraint L_3 outperforms all the other models on both Levy/Holt Dataset and Berant Dataset with AUC of PRC, while EGT2- L_1 performs best with AUC of ROC. All of three soft transitivity constraints boost the performance of local model on all evaluation metrics, which shows that making use of transitivity rule between entailment relations improves the local entailment graph. EGT2- L_1 or EGT2- L_3 performs better than EGT2- L_2 , which indicates that involving the premises $a \rightarrow b$ and $b \rightarrow c$ into loss function is also important for using transitivity constraints.

The Precision-Recall Curves of different meth-

ods and the Precision-Recall Point of Berant et al. (2011) on the two evaluation datasets are shown in Figure 2(a) and 2(b) respectively. The local and global models of EGT2 consistently outperform previous state-of-the-art methods on all levels of precision and recall, which indicates the effect of our local model based on textual entailment and global soft constraints based on transitivity. The EGT2-Local achieves slightly higher precision than global models in the range $recall < 0.5$, but its precision drops quickly if we require higher recall and therefore leads to worse performance than global models. The result indicates that global models with transitivity constraints gain significant improvement on recall with far less expense on precision than EGT2-Local.

5.2 How the local model fine-tuning works?

As described in Section 4.4, a new corpus is generated for fine-tuning the local model. We claim that the fine-tuning corpus helps to improve the performance of EGT2-Local by adapting it to the special sentence pattern by S , rather than offering additional data to fit the distribution of target datasets as traditional training datasets do. To prove this, we also test a simple supervised method, labelled as Local-Sup, which fits a 2-layers feedforward neural network on the fine-tuning corpus with cosine similarity, Weed, Lin and BInc scores as features. If the corpus acts as training dataset, the performance of Local-Sup should be obviously better than its unsupervised features.

As shown in Table 2, Local-Sup does not perform significantly better on Levy/Holt Dataset, and even worse on Berant Dataset than BInc, which is one of the inputting features of Local-Sup. The result illustrates the difference between the fine-tuning corpus and the evaluation datasets, and shows that the corpus plays a role as pattern adapting corpus rather than training dataset.

5.3 Why are global constraints helpful?

In Section 1, we expect that the improvement of soft transitivity constraints is attributed to the alleviation of data sparsity in corpus. To examine the sparsity before and after the applying of transitivity constraints, we count how many the positive and negative entailment relations in the Levy/Holt test set exactly appear in the local and global entailment graph respectively, and show the counting results in Table 3. All three soft transitivity constraints help to find more entailment relations than




Figure 2: The Precision-Recall Curves of different methods on (a) Levy/Holt Dataset and (b) Berant Dataset. The result of [Berant et al. \(2011\)](#) is shown as a point, as they generate entailment graphs without weight.

Table 3: The number of testing examples appearing in entailment graphs learnt by corresponding models.

Methods	Positive #	Negative #
EGT2-Local	378	75
EGT2- L_1	642	174
EGT2- L_2	783	277
EGT2- L_3	685	190

local entailment graph and therefore achieve better performance on the evaluation datasets. Although EGT2- L_2 finds the most entailment relations in the dataset in global stage, it finds more negative examples concurrently and thus performs worse than L_1 and L_3 as shown in Table 2. On the other hand, EGT2- L_1 and EGT2- L_3 obtain more proportions of positive examples by considering premise relations during the gradient calculation. The low confidence of hypothesis relationship $W_{a,c}$ should be helpful to detect spurious premises $W_{a,b}$ and $W_{b,c}$. Therefore, EGT2- L_3 slightly outperforms EGT2- L_1 as the gradients of $W_{a,b}$ and $W_{b,c}$ in L_3 are related to the hypothesis relationship $W_{a,c}$.

We have also applied the soft transitivity constraints on the local graph with BInc and [Hosseini et al. \(2019\)](#), but observed only slightly improvement of performance, as $.155 \rightarrow .157$ and $.167 \rightarrow .170$ for EGT2- L_3 on PRC of Levy/Holt Dataset respectively. Comparing it with the significant improvement based on EGT2-Local, we claim that the high-quality local entailment graphs are the basis of effective soft transitivity constraints.

The previous cross-graph soft constraint and paraphrase resolution soft constraint proposed in

Table 4: Model performance on the directional section of Levy/Holt Dataset.

Methods	PRC	ROC
BInc	.038	.567
Hosseini18	.038	.564
Hosseini19-Local	.040	.579
EGT2-Local	.176	.654
EGT2- L_3	.171	.696

[Hosseini et al. \(2018\)](#) have shown improvement of performance based on their local graphs. However, due to the distinct distribution and scales of local scores, their constraints are computationally unavailable on our local graphs, partially due to the high overhead for cross-graph calculation.

5.4 Does EGT2 learn directional entailment?

Generally, the logical entailment should be directional which makes it different from *paraphrase*. Although EGT2 significantly improves the performance on two datasets, it is unclear whether the improvement comes from the directional entailment cases, or only paraphrasing ones, as the local LM might be strong in recognizing paraphrases but weak in recognizing directional entailment ([Cabezudo et al., 2020](#)). To examine how EGT2 works under directional cases, we eliminate those paraphrase predicate pairs $a \rightarrow b$ with label $l \in \{True, False\}$ from Levy/Holt test dataset, if the corresponding $b \rightarrow a$ is also appearing and labelled as l in the test dataset. The rest directional section of Levy/Holt Dataset contains 8,140 examples (753 positive and 7,387 negative). We

expect that this section should be more challenging as unidirectional paraphrase becomes unavailable.

We report the model performance on the directional section of Levy/Holt Dataset in Table 4. We can see that previous baselines do not perform well on AUC of PRC, which indicate that it is difficult for them to reach *precision* > 0.5. Meanwhile, EGT2-Local and EGT2- L_3 outperform all baselines on the directional section of Levy/Holt Dataset. Unsurprisingly, all models’ AUC scores on the directional section become lower compared on the original Levy/Holt Dataset, showing the challenges of directional entailment inference. Two EGT2 variants maintain high performance, which proves that our local model can learn to capture directional predicate entailment better than distributional baselines, and the global soft constraint also helps to make directional entailment inference.

5.5 Error Analysis

We randomly sample and analyze 100 false positive (FP) examples and 100 false negative (FN) examples from Levy/Holt test set according to predictions by EGT2- L_3 . We manually setup the decision threshold as 0.574 to make the precision level close to 0.76, which is the same as Berant et al. (2011). The major error types are shown in Table 5. Although the global constraint is used, about half of FN errors are due to the data sparsity where the entailment relations are not found in the entailment graph. When compared with the results in Hosseini et al. (2018), EGT2- L_3 reduces the ratio of *Sparsity* in FN errors from 93% to 46% with stronger alleviation ability of data sparsity. About a quarter of FN are caused by the *Under-weighted Relations* in the graph, where EGT2 finds the entailment relations but gives them scores lower than the threshold. The rest of FN are related to *Dataset Wrong Labels* which happens when the predicates are indeed entailed by others but labelled as negative, or the predicate pairs are incomplete.

Most of FP errors are caused by the *Spurious Correlation* as these relations are too fraudulent for EGT2 to see through their spurious relationships and consequently given high scores. A few FP errors are caused by *Lemma-based Processing* in LM inevitably, but the ratio still reduces from 12% in Hosseini et al. (2018) to 5%. The result indicates that our fine-tuned LM can handle the predicates even with similar surface forms and contexts better than parsing-based distributional local features.

Table 5: The major error types of false positive and false negative predictions by EGT2- L_3 in Levy/Holt test set, with predicted scores in the parentheses.

Error Types	Examples
<i>False Negative</i>	
Sparsity (46%)	Pain relieves by application of Chloroform. → Chloroform reduces pain. (0.0)
Under-weighted Relations (23%)	The Druids build the Stonehenge. → The Druids construct the Stonehenge. (0.558)
Dataset Wrong Labels (31%)	Salicylates reduces pain. → Salicylates is given for pain. (0.034)
<i>False Positive</i>	
Spurious Correlation (68%)	The cat sleeps on a fur. → The cat has a fur. (0.683)
Lemma-based Process (5%)	Lincoln comes to New York. → Lincoln comes from New York. (0.867)
Dataset Wrong Labels (27%)	The lamps are made of metal. → The lamps are made of metal. (1.0)

6 Conclusions

In this paper, we propose a novel typed entailment graph learning framework, EGT2, which uses language models fine-tuned on textual entailment tasks to calculate local entailment scores and applies soft transitivity constraints to learn global entailment graphs in gradient-based method. The transitivity constraints are achieved by carefully designed loss functions, and effectively boost the quality of local entailment graphs. By using the fine-tuned local LM and global soft constraints, EGT2 does not rely on distributional features, and can be easily applied to large-scale graphs. Experiments on standard benchmark datasets show that EGT2 achieves significantly better performance than existing state-of-the-art entailment graph methods.

Acknowledgements

This work is supported in part by National Key R&D Program of China (No. 2020AAA0106600) and NSFC (62161160339). We would like to thank the anonymous reviewers and action editors for their helpful comments and suggestions.

References

- Jonathan Berant, Noga Alon, Ido Dagan, and Jacob Goldberger. 2015. [Efficient global learning of entailment graphs](#). *Computational Linguistics*, 41(2):221–263.
- Jonathan Berant, Ido Dagan, Meni Adler, and Jacob Goldberger. 2012. [Efficient tree-based approximation for entailment graph learning](#). In *Proceedings of the 50th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 117–125, Jeju Island, Korea. Association for Computational Linguistics.
- Jonathan Berant, Ido Dagan, and Jacob Goldberger. 2011. [Global learning of typed entailment rules](#). In *Proceedings of the 49th Annual Meeting of the Association for Computational Linguistics: Human Language Technologies*, pages 610–619, Portland, Oregon, USA. Association for Computational Linguistics.
- Kurt Bollacker, Colin Evans, Praveen Paritosh, Tim Sturge, and Jamie Taylor. 2008. Freebase: a collaboratively created graph database for structuring human knowledge. In *Proceedings of the 2008 ACM SIGMOD international conference on Management of data*, pages 1247–1250.
- Marco Antonio Sobrevilla Cabezudo, Marcio Inácio, Ana Carolina Rodrigues, Edresson Casanova, and Rogério Figueredo de Sousa. 2020. Natural language inference for portuguese using bert and multilingual information. In *International Conference on Computational Processing of the Portuguese Language*, pages 346–356. Springer.
- YL Cun, L Bottou, G Orr, and K Muller. 1998. Efficient backprop, neural networks: Tricks of the trade. *Lecture notes in computer sciences*, 1524:5–50.
- Maayan Geffet and Ido Dagan. 2005. [The distributional inclusion hypotheses and lexical entailment](#). In *Proceedings of the 43rd Annual Meeting of the Association for Computational Linguistics (ACL'05)*, pages 107–114, Ann Arbor, Michigan. Association for Computational Linguistics.
- Liane Guillou, Sander Bijl de Vroe, Mohammad Javad Hosseini, Mark Johnson, and Mark Steedman. 2020. [Incorporating temporal information in entailment graph mining](#). In *Proceedings of the Graph-based Methods for Natural Language Processing (TextGraphs)*, pages 60–71, Barcelona, Spain (Online). Association for Computational Linguistics.
- Madan M Gupta and J11043360726 Qi. 1991. Theory of t-norms and fuzzy inference methods. *Fuzzy sets and systems*, 40(3):431–450.
- Pengcheng He, Xiaodong Liu, Jianfeng Gao, and Weizhu Chen. 2020. Deberta: Decoding-enhanced bert with disentangled attention. *arXiv preprint arXiv:2006.03654*.
- Xavier Holt. 2018. Probabilistic models of relational implication. *arXiv preprint arXiv:1907.12048*.
- Mohammad Javad Hosseini, Nathanael Chambers, Siva Reddy, Xavier R. Holt, Shay B. Cohen, Mark Johnson, and Mark Steedman. 2018. [Learning typed entailment graphs with global soft constraints](#). *Transactions of the Association for Computational Linguistics*, 6:703–717.
- Mohammad Javad Hosseini, Shay B. Cohen, Mark Johnson, and Mark Steedman. 2019. [Duality of link prediction and entailment graph induction](#). In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 4736–4746, Florence, Italy. Association for Computational Linguistics.
- Mohammad Javad Hosseini, Shay B Cohen, Mark Johnson, and Mark Steedman. 2021. Open-domain contextual link prediction and its complementarity with entailment graphs. In *Findings of the Association for Computational Linguistics: EMNLP 2021*, pages 2790–2802.
- Tushar Khot, Ashish Sabharwal, and Peter Clark. 2018. Scitail: A textual entailment dataset from science question answering. In *Thirty-Second AAAI Conference on Artificial Intelligence*.
- Erich Peter Klement, Radko Mesiar, and Endre Pap. 2013. *Triangular norms*, volume 8. Springer Science & Business Media.
- Omer Levy and Ido Dagan. 2016. [Annotating relation inference in context via question answering](#). In *Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers)*, pages 249–255, Berlin, Germany. Association for Computational Linguistics.
- Tao Li, Vivek Gupta, Maitrey Mehta, and Vivek Sriku-mar. 2019. [A logic-driven framework for consistency of neural models](#). In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 3924–3935, Hong Kong, China. Association for Computational Linguistics.
- Dekang Lin. 1998. [Automatic retrieval and clustering of similar words](#). In *36th Annual Meeting of the Association for Computational Linguistics and 17th International Conference on Computational Linguistics, Volume 2*, pages 768–774, Montreal, Quebec, Canada. Association for Computational Linguistics.
- Dekang Lin and Patrick Pantel. 2001. Discovery of inference rules for question-answering. *Natural Language Engineering*, 7(4):343–360.
- Xiao Ling and Daniel S Weld. 2012. Fine-grained entity recognition. In *Twenty-Sixth AAAI Conference on Artificial Intelligence*.

- Nick McKenna, Liane Guillou, Mohammad Javad Hosseini, Sander Bijl de Vroe, Mark Johnson, and Mark Steedman. 2021. Multivalent entailment graphs for question answering. *arXiv preprint arXiv:2104.07846*.
- Sebastian Padó, Daniel Cer, Michel Galley, Dan Jurafsky, and Christopher D Manning. 2009. Measuring machine translation quality as semantic equivalence: A metric based on entailment features. *Machine Translation*, 23(2):181–193.
- Terence Parsons. 1990. Events in the semantics of english: A study in subatomic semantics.
- Amarnath Pathak, Riyanka Manna, Partha Pakray, Dipankar Das, Alexander Gelbukh, and Sivaji Bandyopadhyay. 2021. Scientific text entailment and a textual-entailment-based framework for cooking domain question answering. *Sādhanā*, 46(1):1–19.
- Ellie Pavlick, Pushpendre Rastogi, Juri Ganitkevitch, Benjamin Van Durme, and Chris Callison-Burch. 2015. [PPDB 2.0: Better paraphrase ranking, fine-grained entailment relations, word embeddings, and style classification](#). In *Proceedings of the 53rd Annual Meeting of the Association for Computational Linguistics and the 7th International Joint Conference on Natural Language Processing (Volume 2: Short Papers)*, pages 425–430, Beijing, China. Association for Computational Linguistics.
- Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J. Liu. 2020. [Exploring the limits of transfer learning with a unified text-to-text transformer](#). *Journal of Machine Learning Research*, 21(140):1–67.
- Siva Reddy, Mirella Lapata, and Mark Steedman. 2014. [Large-scale semantic parsing without question-answer pairs](#). *Transactions of the Association for Computational Linguistics*, 2:377–392.
- Martin Schmitt and Hinrich Schütze. 2021a. Continuous entailment patterns for lexical inference in context. *arXiv preprint arXiv:2109.03695*.
- Martin Schmitt and Hinrich Schütze. 2021b. [Language models for lexical inference in context](#). In *Proceedings of the 16th Conference of the European Chapter of the Association for Computational Linguistics: Main Volume*, pages 1267–1280, Online. Association for Computational Linguistics.
- Idan Szepktor and Ido Dagan. 2008. [Learning entailment rules for unary templates](#). In *Proceedings of the 22nd International Conference on Computational Linguistics (Coling 2008)*, pages 849–856, Manchester, UK. Coling 2008 Organizing Committee.
- Julie Weeds and David Weir. 2003. [A general framework for distributional similarity](#). In *Proceedings of the 2003 Conference on Empirical Methods in Natural Language Processing*, pages 81–88.
- Adina Williams, Nikita Nangia, and Samuel Bowman. 2018. [A broad-coverage challenge corpus for sentence understanding through inference](#). In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers)*, pages 1112–1122, New Orleans, Louisiana. Association for Computational Linguistics.
- Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Rémi Louf, Morgan Funtowicz, et al. 2019. Huggingface’s transformers: State-of-the-art natural language processing. *arXiv preprint arXiv:1910.03771*.
- Masashi Yoshikawa, Koji Mineshima, Hiroshi Noji, and Daisuke Bekki. 2019. Combining axiom injection and knowledge base completion for efficient natural language inference. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pages 7410–7417.
- Congle Zhang and Daniel S. Weld. 2013. [Harvesting parallel news streams to generate paraphrases of event relations](#). In *Proceedings of the 2013 Conference on Empirical Methods in Natural Language Processing*, pages 1776–1786, Seattle, Washington, USA. Association for Computational Linguistics.

A Algorithm for Sentence Generator

Algorithm 1 The sentence generator S .

Require: $p = (w_{p,1}.i_{p,1}, w_{p,2}.i_{p,2}, t_1, t_2)$: a typed predicate;

Ensure: Sentence $S(p)$

```
1: if Order of  $(t_1, t_2)$  is equal to graph types then
2:   Actor1 = concat( $t_1$ , "A")
3:   Actor2 = concat( $t_2$ , "B")
4: else
5:   Actor1 = concat( $t_1$ , "B")
6:   Actor2 = concat( $t_2$ , "A")
7: end if
8: if The first word of  $w_{p,1}$  or  $w_{p,2}$  is not a verb then
9:    $w_{p,1}$  = concat("is",  $w_{p,1}$ )
10:   $w_{p,2}$  = concat("is",  $w_{p,2}$ )
11: end if
12: Active1 = Boolean( $i_{p,1} = 1$ )
13: Active2 = Boolean( $i_{p,2} = 1$ )
14: MinLen = min(Length( $w_{p,1}$ ), Length( $w_{p,2}$ ))
15: MML = max  $i$ , s.t.  $w_{p,1}[1:i] = w_{p,2}[1:i]$ 
16: Pathway = Boolean(MML = MinLen)
17: if Active1 and Active2 then
18:   if Pathway then
19:     return concat(Actor1, "and", Actor2,  $w_{p,1}[1$ :
MinLen])
20:   end if
21:   return concat(Actor1, "and", Actor2,  $w_{p,1}[1$ )
22: end if
23: if Active1 and not Active2 then
24:   if Pathway then
25:     Act =  $w_{p,1}$ 
26:     if Length( $w_{p,1}$ ) < MinLen then
27:       Act =  $w_{p,2}$ 
28:     end if
29:     return concat(Actor1, Act, Actor2)
30:   end if
31:   return concat(Actor1,  $w_{p,1}$ , "Something",
 $w_{p,2}[MML+1:]$ , Actor2)
32: end if
33: if Active2 and not Active1 then
34:   if The first words of  $w_{p,1}$  is verb then
35:     return concat(Actor1, Reverse(
 $w_{p,2}[MML:]$ ), "to",  $w_{p,1}$ , Actor2)
36:   end if
37:   return concat(Actor1, Reverse( $w_{p,2}$ ),
 $w_{p,1}[MML:]$ , Actor2)
38: end if
39: if Pathway then
40:   return concat(Actor1, Passive( $w_{p,1}$ ),
 $w_{p,2}[MML:]$ , Actor2)
41: end if
42: return concat("Something",  $w_{p,1}$ , Actor1,
 $w_{p,2}[MML:]$ , Actor2)
```

B Additional Implementation Details

We select the SGD learning rate α from $\{0.02, 0.05, 0.1\}$, the number of training epochs from $\{2, 3, 5, 7\}$, the coefficient λ from $\{0.5, 1, 2\}$, and the confidence threshold ϵ from $\{0.005, 0.01, 0.02\}$. We manually tune the hyper-parameters based on the AUC of PRC on Levy/Holt validation dataset, which is .327 corresponding to our settings.

Under our experiment settings, one training epoch costs about 4 hours on an NVIDIA A40 GPU.